



Flexible Additive and Primer

Features

- ◆ Versatile and Durable
- ◆ Increases Bond Strength
- ◆ Improves Water Resistance
- ◆ Improves Flexibility
- ◆ Seals and Primes
- ◆ Use with Porous Substrates

A universal flexible additive and primer. As an additive, the product provides enhanced performance to adhesives and grouts not previously polymer modified. As a primer it is a sealing agent suitable for porous surfaces such as a variety of building substrates, including plaster, timber, brick and block work.



Internal Floors



Lifetime Guarantee



Manufactured by **Instarmac Group plc**

Danny Morson Way, Birch Coppice Business Park, Dordon, Tamworth B78 1SE

Tel: +44 (0) 1827 871871; Fax: +44 (0) 1827 874466; email@instarmac.co.uk; www.instarmac.co.uk

Version 11/07.WHD1954

Flexible Additive and Primer

INFORMATION

Ultra Prime IT FP as an additive has been designed to give enhanced performance to the Ultra adhesives and grouts that have not been previously polymer modified. The product increases bond strength and flexural performance whilst reducing water penetration. It is suitable for areas of substrate movement, i.e. green screeds, boarded floors, under floor heating, porous and moisture sensitive substrates. Ultra Prime IT FP can also be used as an acrylic surface conditioner.

Ultra Prime IT FP as a primer has been designed to be a universal priming/sealing agent. It is suitable for a variety of building substrates, including plaster, timber, brick and block work (i.e. porous surfaces).

SURFACE PREPARATION

Ensure that the surface of the substrate is clean, dry and firm. It should be free of dust, dirt, oil and grease or any other contaminants. Please ensure that the surface is strong enough to support the weight of the tile and adhesive.

MIXING AND APPLICATION

As a primer: Ultra Prime IT FP should be diluted in the approximate ratio of 3 parts clean water to 1 part product, when applied to the surface of the substrate. Apply enough Ultra Prime IT FP on the surface to create a translucent film.

As an additive: Use a mixture of 1 part Ultra Prime IT FP to 1 part clean water or as indicated on the packaging of the product added to. This solution should then be added slowly to the adhesive powder until the required consistency is achieved. Note: The use of Ultra Prime IT FP will slow the set rate of the adhesive.

As a part of Ultra ProFlex 2part: Use the entire contents of this bottle neat. Do not dilute or use any additives.

CLEANING

Tools should be thoroughly cleaned in water to remove excess material immediately after use.

RELATED PRODUCTS

- Ultra ProFlex SP – Single Part Rapid Set Flexible Tile Adhesive
- Ultra ProRapid PB – Rapid Setting Tile Adhesive
- Ultra ProRapid RS – Rapid Setting Porcelain Tile Adhesive
- Ultra ProSet SS – Standard Set Tile Adhesive
- Ultra ProFlex SP+ES – Extended Set Single Part Flexible Tile Adhesive
- Ultra ProFlex 2part – Highly Flexible Rubber Crumb Adhesive

TECHNICAL DATA

Packaging:	2.5 litre plastic bottle.
Storage:	Store in airtight containers between 5°C and 30°C. Protect from frost and direct sunlight. Do not use storage vessels or pipe work made of aluminium, copper or their alloys. Bulk tanks should be regularly cleaned and sterilized.
Shelf Life:	6 months in the above conditions.
Colours:	White/off-white.

QUALITY ASSURANCE

All products are manufactured in a plant the quality management system of which is certified/registered as being in conformity with BS EN ISO 9001:2000, ISO 14001:2004 and OHSAS 18001. ULTRA products are guaranteed against defective materials and manufacture and will be replaced or money refunded if the goods do not comply with our promotional literature. We cannot however accept responsibility arising from the application or use of our products because we have no direct or continuous control over where and how our products are used. All ULTRA products are sold subject to our conditions of sale, copies of which may be obtained upon request.

HEALTH & SAFETY

Please ensure that the appropriate PPE is used when preparing, mixing and applying products. Always wash hands before consuming food or smoking and make sure that materials are kept safely out of reach of children and animals. The use of impermeable gloves, goggles and/or face shields are recommended. Work in well ventilated areas. Please dispose of packaging and waste appropriately.

A full Material Safety Data Sheet relating to this product is available from www.instarmac.co.uk.

IRRITANT

- R43 May cause sensitisation by skin contact
- S24 Avoid contact with skin
- S37 Wear suitable gloves
- S46 If swallowed, seek medical advice immediately and show this container or label
- S56 Dispose of this material and its container to hazardous or special waste collection point.