



# PAVEJOINT

## Ready to Use Jointing Compound

### FOR DRIVES, PATHS & PATIOS

#### Preparation:

Depending on the porosity and surface texture of the paving in use, it is advisable to follow the below steps on a small sample area for compatibility, to ensure the paving does not stain.

PAVEJOINT's colour comes from natural aggregates and can give a different appearance alongside different coloured paving. Check the colour against your chosen paving by opening the tub and comparing.

PAVEJOINT is unsuitable for use in long-term/permanent water immersion, but will withstand wet-dry weather cycles. Paved areas, beds and joints must be well drained to avoid standing water for long periods.

Protect against rainfall until hardened, and do not apply in temperatures below 5°C. Curing time will depend on temperature - cold weather retards, warm weather accelerates.

PAVEJOINT's full cure can take up to 28 days.

#### Application:

Ensure joints are no less than 2mm wide at the narrowest point, and no greater than 25mm. Ensure all paving is clean, dry and that all joints are free from debris (it is typical for most porous blocks to exhibit light inherent staining).

Stir the bucket contents to ensure that all components are thoroughly blended.

Apply PAVEJOINT to the surface and sweep into the joints.

Ensure that PAVEJOINT has been applied to the entire joint depth.

Wash down the entire surface of the paving using a hosepipe, in an organised manner (it is advisable to direct water flow towards natural drainage points), ensuring that all the PAVEJOINT is removed from the paving's surface.

Where PAVEJOINT remains in the fine pores of open textured blocks, use a fine bristled broom and brush thoroughly in different directions. Spray more water onto the paving and remove excess PAVEJOINT.

**NOTE:** When the surface is wet, the paving may look clean, however this is not always the case. It is the responsibility of the applicator to ensure they are satisfied that the paving has been thoroughly cleaned.

In areas of ponding, more care should be taken to clean paving. Remove residue by brushing, and thoroughly rinse the area.

If any light staining remains when the surface has dried, this can be removed by carefully power washing the paving after 7 days.



#### Features & Benefits

- Contains recycled material
- Just sweep into joints and water
- No wastage
- Will accommodate joint sizes from 2mm-25mm
- Non-shrink and Non-crack
- Weed resistant
- Enables paving to be re-used
- Suitable for use with all paving types



#### Related Products

- **Ultrascape DRIVE REVIVE** Driveway Paint
- **Ultrascape STAIN AWAY** Driveway De-greasant
- **Ultrascape SEAL & STOP** Solvent-free Paving Sealer
- **Ultrascape FIX OR GROUT** Paving Bedding Mortar or Grout
- **Ultrascape RAPID REPAIR** Concrete Repair
- **Ultrascape PERMANENT POTHOLE REPAIR** Cold Lay Pothole Repair

continued



# PAVEJOINT

## Ready to Use Jointing Compound

### FOR DRIVES, PATHS & PATIOS

#### Physical Properties:

##### COVERAGE

200x100x50mm with a 3mm Joint = approx. 6m<sup>2</sup> per 20kg tub

450x1450x25mm with a 10mm Joint = approx. 12.5m<sup>2</sup> per 20kg tub

For more detailed coverage information, please visit [www.ultrascape.co.uk](http://www.ultrascape.co.uk) and use our free product calculator, or call us on +44(0)1827 871871. Alternatively, you can email [pavejoint@instarmac.co.uk](mailto:pavejoint@instarmac.co.uk)

##### SHELF LIFE

From date of manufacture in sealed tubs is 12 months.

##### PACKAGING

20kg Buckets (40 buckets to a pallet, delivered shrink-wrapped). Available in Buff and Natural - lid colour denotes product colour.

##### COLOURS

Available in:



\* Print colours should be treated as such, and as merely indicative of the true product colour.

#### Product Details

Initial Set	8 Hours*
Final Set	3 Days*
Final Cure	28 Days*

\* Depending on temperatures – test carried out at 20°C. Cool temperatures retard, warm temperatures accelerate product performance.

### EASY AS “A,B,C”

#### Apply

Pour out contents of bucket

#### Brush

Sweep contents of bucket into joints. Every joint must be completely filled. Ensure all excess material is cleared from surface of paving

#### Clean

Soak the joints using a hosepipe set to spray. All residue MUST be cleaned from the surfaces completely using water and a stiff brush. Protect against rainfall until hardened, to ensure a professional smooth finish.



#### Contact Us

Instarmac® Group plc, Birch Coppice Business Park, Danny Morson Way, Dordon, Tamworth, Staffordshire, B78 1SE, United Kingdom

Tel: +44 (0) 1827 872244 Fax: +44 (0) 1827 874466

Email: [email@instarmac.co.uk](mailto:email@instarmac.co.uk) Order: [orders@instarmac.co.uk](mailto:orders@instarmac.co.uk) Website: [www.instarmac.co.uk](http://www.instarmac.co.uk)

Ultrascape products are guaranteed against defective materials and manufacture, and will be replaced or money refunded if the goods do not comply with our promotional literature. We cannot however accept any liability arising from the application or use of our products because we have no direct or continuous control over where and how our products are used. All products are sold subject to our conditions of sale, copies of which may be obtained on request.

An **INSTARMAC**® Brand